



TRV-1/4



PES-QD

PES-1/4



JPV-(Pump Series)



ATC-27

GHF-BR



GHF-PL

HPG-V/H+(Pressure Max Value)



Thermal Relief Valve

Code No.	Max Pressure	Inlet	Outlet	Bypass
TRV-1/4	200psi/15bar	1/4" Male	N/A	N/A
TRV-1/2	200psi/15bar	1/2" Male	N/A	N/A

* TRV For a pump that install with a internal bypass unloader, when in bypass mode the recirculating water in the pump head will heat up very quickly, when the water TEMP. above 60°C/140°F the TRV WAX plug will getting soft and open to relieve the hot water, after the system cooling down the plug will reset.

Pressure Switch

Code No.	Max Pressure	Inlet	Outlet	Type
PES-1/4	7200psi/500bar	1/4" Male	N/A	Normally Open/Close
PES-QD	4000psi/275bar	3/8" QD Plug	3/8" QD	Normally Open/Close

* PES A kind of pressure sensor, connect to the pump or system high pressure area, by the pressure difference will active the micro switch and produce the ON-OFF signal, realize the system auto control. Activation pressure 435psi/30bar, Max 5amps, 250V. Max working TEMP 90°C/194°F

Jetter Pulse Valve

Code No.	Max Pressure	Fitting Size
JPV-(Pump Series)	4000psi/275bar	Same as pump valve plug
JPV-DBD/OBD/OBO/OBF	4000psi/275bar	Same as pump valve plug

* JPV Use to convert the high pumps into a sewer cleaning pump, it install on the pump central intaking valve, when fully engaged the pin it stops the valve from operating, and create the flow pulsations on demand to improve nozzle movement and cleaning power in sewer cleaning applications.

Auto Throttle controller

Code No.	Max Pressure	Fitting Size	Stroke
ATC-27	4000psi/275bar	1/4" Male	7 mm

* ATC Engine auto throttle controller reduces the engine RPM when pump is in by-pass, it reduced engine wear and fuel consumption and prolongs the pump life, since the engine is not continually running at full RPM.

Garden Hose Nipple Fitting

Code No.	Fitting Size	Thread Type
GHF-BR	3/4" Male	BSP/NH
GHF-PL	3/4" Male	BSP/NH

* GHF Standard Europe type brass and plastic garden hose quick disconnect nipple fitting, for quick and easy to install and disconnect the garden hose.

High Pressure Gauge

Code No.	Pressure Range	Rating	Fitting Size	Thread Type
HPG-V25M	0-25MPa	PSI-MPa	1/4" Male	BSPT or NPT
HPG-V40M	0-40MPa	PSI-MPa	1/4" Male	BSPT or NPT
HPG-V60M	0-60MPa	PSI-MPa	1/4" Male	BSPT or NPT
HPG-V600B	0-600Bar	PSI-MPa	1/4" Male	BSPT or NPT

* V-Vertical * H-Horizontal

2400-2600PSI GAS PRESSURE WASHER

5.5-6.5HP Vertical Gasoline Engine, High Consumer Grade



Standard Features:

- Semi-professional grade brass or aluminum forged axial pump, built with thermal protection and detergent injector.
- Performance proven vertical gas engine, EPA and EU V certified.
- Powder coating frame, bolt on handle include with gun and hose hook.
- 12" non-flat plastic wheel, assembly on frame with no tool required.
- Professional trigger gun include with 20" stainless steel lance.
- 4tips 1/4" quick nozzle include 0, 25, 40 degree and black soap nozzle.
- ID1/4" (6.4mm) x 25FT (8m) thermal plastic hose, M22 swivel fitting.

Technical Specifications

Model	DCAC-16/BJV	DCAC-18/BJV
Max Pressure	2400psi/166bar	2600psi/179bar
Max Flow	2.2gpm/9.5lpm	2.5gpm/9.6lpm
Pump Model	DAC-13063AV	DAC-13071AV
Power And Type	5.5hp/179cc, Vertical	6.5hp/196cc, Vertical
Shipping Size	67x41.5x55cm	67x41.5x55cm
Shipping Weight	35kgs	35kgs
20FT/40FT/40HQ	160/320/320pcs	160/320/320pcs

2600PSI GAS PRESSURE WASHER

6.5HP Horizontal Gasoline Engine, High Consumer Grade



Standard Features:

- Semi-professional grade brass or aluminum forged axial pump, built with thermal protection and detergent injector.
- Performance proven horizontal gas engine, EPA and EU V certified.
- Powder coating frame, bolt on handle include with gun and hose hook.
- 10" Solid Non-flat wheel with no bearing.
- Professional trigger gun include with 20" stainless steel lance.
- 5tips 1/4" QD nozzle include 0, 15, 25, 40 degree and black soap nozzle.
- ID1/4" (6.4mm) x 25FT (8m) thermal plastic hose, M22 swivel fitting.

Technical Specifications

Model	DCAC-16/BJB
Max Pressure	2600psi/179bar
Max Flow	2.5gpm/9.6lpm
Pump Model	DAC-13071A, Brass or aluminum
Power And Type	6.5hp/196cc, Horizontal OHV
Shipping Size	67x41.5x55cm
Shipping Weight	35kgs
20FT/40FT/40HQ	160/320/320pcs



COMMERCIAL Cold Water GAS Pressure Washer

2800 GAS PRESSURE WASHER

6.5-7HP Gasoline Engine, Axial Pump, Commercial Grade



Standard Features:

- Commercial grade brass or aluminum forged axial pump, built with thermal protection and detergent injector.
- Performance proven horizontal gas engine, EPA and EU V certified.
- Powder coating frame, bolt on handle including with gun and hose hook.
- 10" Solid Non-flat wheel with no bearing.
- Professional trigger gun include with 20" stainless steel lance.
- 5tips 1/4" QD nozzle include 0, 15, 25, 40 degree and black soap nozzle.
- 1/4" ID (6.4mm) x 25FT (8m) thermal plastic hose, M22 swivel fitting.

Technical Specifications

Model	DCAA-19/11JB	DCAC-19/13JB
Max Pressure	2800psi/193bar	2800psi/193bar
Max Flow	3.0gpm/11.3lpm	3.4gpm/12.8lpm
Pump Model	DAA-15063A, Brass	DAC-15071A, Brass
Power And Type	6.5hp/196cc, OHV	7.0hp/212cc, OHV
Shipping Size	67x41.5x55cm	67x41.5x55cm
Shipping Weight	36kgs	36kgs
20FT/40FT/40HQ	160/320/320pcs	160/320/320pcs



2800PSI GAS PRESSURE WASHER

6.5-7HP Gasoline Engine, Axial Pump, Commercial Grade



Technical Specifications

Model	DCAA-19/11A	DCAA-19/11B	DCAA-19/11E
Max Pressure	2800psi/193bar	2800psi/193bar	2800psi/193bar
Max Flow	3.0gpm/11.3lpm	3.0gpm/11.3lpm	3.0gpm/11.3lpm
Pump Model	DAA-15063A, Brass	DAA-15063A, Brass	DAA-15063A, Brass
Power And Type	6.5hp/196cc, OHV	6.5hp/196cc, OHV	6.5hp/196cc, OHV
Shipping Size	71x40x47.5cm	59x41.5x58cm	71x42.5x52.5cm
Shipping Weight	38kgs	37kgs	38kgs
20FT/40FT/40HQ	160/320/320pcs	195/420/420pcs	156/324/405pcs

COMMERCIAL Cold Water GAS Pressure Washer

3000PSI GAS PRESSURE WASHER

6.5-7HP Gas Engine, Triplex Pump, Professional Grade



Standard Features:

- Professional grade brass forged triplex pump, built with detergent injector, option for thermal protection and pressure gauge.
- Performance proven horizontal gas engine, EPA and EU V certified.
- Powder coating frame, bolt on handle include with gun and hose hook.
- 10" Solid Non-flat wheel with no bearing.
- Professional trigger gun include with 20" stainless steel lance.
- 5tips 1/4" QD nozzle include 0, 15, 25, 40 degree and black soap nozzle.
- 1/2" ID (12.7mm) x 30FT (10m) steel braided hose, 3/8" Quick connect.

Technical Specifications

Model	DCC-20/12N
Max Pressure	3000psi/206bar
Max Flow	3.3gpm/13.6lpm
Pump Model	DBC-1507A, Direct drive
Power And Type	6.5hp/196cc, Horizontal OHV
Shipping Size	65x41.5x53.5cm
Shipping Weight	43kgs
20FT/40FT/40HQ	160/320/320pcs



3000PSI GAS PRESSURE WASHER

6.5-7HP Gas Engine, Triplex Pump, Professional Grade



Technical Specifications

Model	DCC-20/12A	DCC-20/12B	DCC-20/12E
Max Pressure	3000psi/206bar	3000psi/206bar	3000psi/206bar
Max Flow	3.3gpm/12.6lpm	3.3gpm/12.6lpm	3.3gpm/12.6lpm
Pump Model	DBC-1507A, Direct drive	DBC-1507A, Direct drive	DBC-1507A, Direct drive
Power And Type	6.5hp/196cc, OHV	6.5hp/196cc, OHV	6.5hp/196cc, OHV
Shipping Size	71x40x47.5cm	59x41.5x58cm	71x42.5x52.5cm
Shipping Weight	41.5kgs	41kgs	41kgs
20FT/40FT/40HQ	160/344/420pcs	195/420/420pcs	156/324/405pcs

COMMERCIAL Cold Water GAS Pressure Washer

3400-3600PSI GAS PRESSURE WASHER

9-13HP Gas Engine, Triplex Pump, Professional Grade



Standard Features:

- Professional grade brass forged triplex pump, built with detergent injector, option for thermal protection and pressure gauge.
- Performance proven horizontal gas engine, EPA and EU V certified.
- All cover type powder coating frame, include with gun and hose hook.
- 13" pneumatic wide ride wheel with bearing load.
- Professional trigger gun include with 20" stainless steel lance.
- 5tips 1/4" OD nozzle include 0, 15, 25, 40 degree and black soap nozzle.
- ID5/16" (8mm) x 30FT (10m) steel braided hose, 3/8" Quick connect.



PUMP MODEL	MAX FLOW		MAX PRESSURE		ENGINE POWER		WEIGHT		SHIPPING SIZE	
	gpm	lpm	psi	bar	hp	cc	kg	cm		
DCC-23/15NG	4.0	15	3400	235	9.0	270	60	77x50x62		
DCC-24/17NG	4.5	17	3600	248	13.0	385	68	77x50x62		



3400-3600PSI GAS PRESSURE WASHER

9-13HP Gas Engine, Triplex Pump, Professional Grade



Model	DCC-23/15AG	DCC-24/17AG
Max Pressure	3400psi/235bar	3600psi/248bar
Max Flow	4.0gpm/15lpm	4.5gpm/17lpm
Pump Model	DBC-15085A, Direct Drive	DBC-1510A, Direct Drive
Power And Type	9hp/270cc, OHV	13hp/390cc, OHV
Nozzle	5tips, QD Nozzle	5tips, QD Nozzle
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Gun And Lance	Trigger Gun, 20" Lance	Trigger Gun, 20" Lance
Frame and wheel	Handle folding, 13" pneumatic	Handle folding, 13" pneumatic
Detergent Injector	Built on pump, downstream	Built on pump, downstream
Shipping Size	79x50x60cm	79x50x60cm
Shipping Weight	58kgs	64kgs



3400-3600PSI GAS PRESSURE WASHER

9-13HP Gas Engine, Triplex Pump, Professional Grade



Model	DCC-23/15D	DCC-24/17D
Max Pressure	3400psi/235bar	3600psi/248bar
Max Flow	4.0gpm/15lpm	4.5gpm/17lpm
Pump Model	DBC-1508A, Direct Drive	DBC-1510A, Direct Drive
Power And Type	9hp/270cc, OHV	13hp/390cc, OHV
Start Type	Key Start, Battery 12x/20ah	Key Start, Battery 12x/20ah
Nozzle	5tips, QD Nozzle	5tips, QD Nozzle
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Gun And Lance	Trigger Gun, 20" Lance	Trigger Gun, 20" Lance
Frame And Wheel	Four wheel, 10" pneumatic	Four wheel, 10" pneumatic
Shipping Size	79x50x60cm	75x50x60cm
Shipping Weight	73kgs	100kgs

COMMERCIAL Cold Water DIESEL Pressure Washer

3600-4000PSI DIESEL PRESSURE WASHER

186-192FE Diesel Engine, Triplex Pump, Direct Drive



Model	DCD-24/17DAD	DCD-27/17DAD
Max Pressure	3600psi/248bar	4000psi/275bar
Max Flow	4.5gpm/17lpm	4.5gpm/17lpm
Pump Model	DBC-1510A, Direct Drive	DBC-1510A, Direct Drive
Power And Type	413cc, Diesel engine	456cc, Diesel engine
Start Type	Key start	Key start
Battery	12V, 20AH	12V, 20AH
Gun And Lance	Trigger gun, 20" lance	Trigger gun, 20" lance
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Nozzle	5tips, QD nozzle	5tips, QD nozzle
Frame Type	All cover, four wheel ride	All cover, four wheel ride
Wheel Size & Type	4 x 10" Pneumatic wheel	4 x 10" Pneumatic wheel
Detergent Injector	Built on pump, down stream	Built on pump, down stream
Anti-vibration	Integrated anti-vibration	Integrated anti-vibration
Thermal Protection	Optional	Optional
Hose Reel	Optional	Optional
Shipping Size	80x53x64cm	80x53x64cm
Shipping Weight	100kgs	100kgs
20FT/40FT/40HQ	84/220/220pcs	84/220/220pcs

5000PSI DIESEL PRESSURE WASHER

292FE Diesel Engine, Gearbox Reduction, Professional Grade



Model	DCF-34/25DRTD
Max Pressure	5000psi/345bar
Max Flow	6.6gpm/25lpm
Pump Model	DBF-1821FG2, Gearbox reduction
Power And Type	967cc, 2 cylinder diesel engine, air cooling
Start Type	Key start
Battery	12V, 20AH
Gun And Lance	Trigger gun, 20" lance
High Pressure Hose	ID8x15m, steel braided
Nozzle	5tips, QD nozzle
Frame Type	All cover, four wheel ride
Wheel Size & Type	4 x 8" heavy load solid rubber wheel, include 2 break wheel
Water Cycle Tank	Stainless steel water cycle tank with floating valve
Anti-vibration	Integrated plate anti-vibration
Hose Reel	Optional
Shipping Size	80x53x64cm
Shipping Weight	100kgs



COMMERCIAL Cold Water GEARBOX Reduction Pressure Washer

3000PSI GAS GEARBOX PRESSURE WASHER

7HP Gasoline Engine, Triplex pump, Gearbox Reduction



Standard Features:

- Professional grade brass forged, gearbox reduction triplex pump, built with detergent injector, option for thermal protection and pressure gauge.
- Performance proven horizontal gas engine, EPA and EU V certified.
- All cover type powder coating frame, include with gun and hose hook.
- 10" pneumatic wheel with bearing load.
- Professional trigger gun include with 20" stainless steel lance.
- 5lips 1/4" quick nozzle include 0, 15, 25, 40 and black soap nozzle.
- ID5/16" (8mm) x 30FT (10m) steel braided hose, 3/8" Quick connect.



PUMP MODEL	MAX FLOW		MAX PRESSURE		ENGINE POWER		WEIGHT		SHIPPING SIZE	
	gpm	lpm	psi	bar	hp	cc	kg	cm		
DCC-20/10GRNF	2.7	10.5	3000	206	7.0	210	47.5	76x40x48.5		



3400-3600PSI GAS GEARBOX PRESSURE WASHER

9-13HP Gasoline Engine, Triplex pump, Gearbox Reduction

Model	DCC-23/11GRD	DCD-24/17GRD
Max Pressure	3400psi/235bar	3600psi/248bar
Max Flow	3.1gpm/11.6lpm	4.5gpm/15lpm
Pump Model	DBC-1514FG2, Gearbox	D6D-1814FG2, Gearbox
Power And Type	9hp/270cc, OHV	13hp/390cc, OHV
Nozzle	5lips, QD Nozzle	5lips, QD Nozzle
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Gun And Lance	Trigger Gun, 20" Lance	Trigger Gun, 20" Lance
Frame Type	All covered, four wheel ride	All covered, four wheel ride
Detergent Injector	Built on pump, downstream	Built on pump, downstream
Hose Reel	Optional	Optional
Shipping Size	80x53x64cm	80x53x64cm
Shipping Weight	63kgs	68kgs



3600-4000PSI DIESEL GEARBOX PRESSURE WASHER

186-192FE Diesel engine, Triplex pump, Gearbox Reduction



Model	DCC-24/17DRD	DCD-27/17DRD
Max Pressure	3600psi/248bar	4000psi/275bar
Max Flow	4.5gpm/17lpm	4.5gpm/17lpm
Pump Model	D6D-1814FG2, Gearbox	D6D-1814FG2, Gearbox
Power And Type	418cc, Diesel engine	456cc, Diesel engine
Nozzle	5lips, QD Nozzle	5lips, QD Nozzle
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Gun And Lance	Trigger Gun, 20" Lance	Trigger Gun, 20" Lance
Frame Type	All covered, four wheel ride	All covered, four wheel ride
Detergent Injector	Built on pump, downstream	Built on pump, downstream
Hose Reel	Optional	Optional
Shipping Size	80x53x64cm	80x53x64cm
Shipping Weight	106kgs	106kgs



COMMERCIAL Cold Water BASE Unit Pressure Washer

2170PSI BASE UNIT PRESSURE WASHER

13-22HP Gasoline Engine, Base Mounting, Belt Drive, Electric Start



Model	DJN-3515	DJN-5015
Max Pressure	2170psi/150bar	2170psi/150bar
Max Flow	9.2gpm/35lpm	13.2gpm/50lpm
Pump Model	DBF-2221B, Belt drive	DBF-2221B, Belt drive
Pump Base	Adjustable	Adjustable
Pulley Size	Driving 85mm, driven 236mm	Driving 95mm, driven 250mm
Pump RPM	1300rpm	1350rpm
Power And Type	13HP Gasoline engine	22HP Gasoline engine
Start Type	Key start	Key start
Battery	12V Battery no include	12V Battery no include
Mounting Base	Strengthen steel plate	Strengthen steel plate
Gun And Lance	Optional	Optional
High Pressure Hose	Optional	Optional
Nozzle	Optional	Optional
Shipping Size	95x50x53cm	95x58x55cm
Shipping Weight	90kgs	110kgs



1600-2900PSI DC MOTOR PRESSURE WASHER

3-5.5-7.5Kw DC Electric Motor, Triplex Pump, Base Mounting



Technical Specifications

Model	DCC-11/12-3D2	DCD-20/13-5D4	DCF-10/35-7D4
Max Pressure	1595psi/110bar	2900psi/200bar	1595psi/110bar
Max Flow	3.43gpm/13lpm	3.43gpm/13lpm	9.25gpm/35lpm
Pump Model	DBC-15085C, Direct drive	D8D-1812C2, Direct drive	DBF-2221, Joint coupling
Power And Type	3Kw, Aluminum cage	5.5Kw, Aluminum cage	7.5Kw, Aluminum cage
DC Voltage	DC+	Optional	Optional
Motor RPM	3000RPM	1500RPM	1500RPM
Gun And Lance	Optional	Optional	Optional
High Pressure Hose	Optional	Optional	Optional
Nozzle	Optional	Optional	Optional

COMMERCIAL Cold Water ELECTRIC Pressure Washer

2200PSI ELECTRIC PRESSURE WASHER

3Kw AC Electric Motor, Triplex pump, Direct Drive



Standard Features:

- Professional grade brass forged triplex pump, built with detergent injector, option for pressure gauge.
- Performance proven heavy duty long lasting electric motor.
- Powder coating frame, include with gun and hose hook.
- 10" Solid Non-flat wheel with no bearing.
- Professional trigger gun include with 20" stainless steel lance.
- 5lips 1/4" QD nozzle include 0, 15, 25, 40 degree and black soap nozzle.
- ID5/16" (8mm) x 30FT (10m) steel braided hose, 3/8" Quick connect.



OPTIONAL



Technical Specifications

Model	DCC-15/10C-3S2	DCC-15/9C-3S4	DCC-15/9C-3T4
Max Pressure	2200psi/152bar	2200psi/152bar	2200psi/152bar
Max Flow	2.82gpm/10.7lpm	2.44gpm/9.22lpm	2.44gpm/9.22lpm
Pump Model	D8C-1507C, Triplex	D8C-1512C, Triplex	D8C-1512C, Triplex
Power And Type	3kw, 220V/50HZ, 2880rpm	3kw, 220V/50HZ, 1450rpm	3kw, 380V/50HZ, 1450rpm
Shipping Size	71x42.5x47.5cm	71x42.5x47.5cm	71x42.5x47.5cm
Shipping Weight	55kgs	35kgs	35kgs

2700-3600PSI ELECTRIC PRESSURE WASHER

4-7.5Kw AC Electric Motor, Triplex pump, Direct Drive



Standard Features:

- Professional grade brass forged triplex pump, built with detergent injector, option for pressure gauge.
- Performance proven heavy duty long lasting electric motor.
- Powder coating frame, include with gun and hose hook.
- 10" Solid Non-flat wheel with no bearing.
- Professional trigger gun include with 20" stainless steel lance.
- 5lips 1/4" QD nozzle include 0, 15, 25, 40 degree and black soap nozzle.
- ID5/16" (8mm) x 30FT (10m) steel braided hose, 3/8" Quick connect.



OPTIONAL



Technical Specifications

Model	DCC-18/10CG-4T4	DCC-20/13CG-5T2	DCC-20/13CG-5T4	DCC-24/15CG-7T4
Max Pressure	2700psi/186bar	3000psi/206bar	3000psi/206bar	3600psi/246bar
Max Flow	2.82gpm/10.7lpm	3.69gpm/13.9lpm	3.5gpm/13.3lpm	4.09gpm/15.5lpm
Pump Model	D8C-1514C2, Triplex	D8C-1509C3, Triplex	D8C-1812C3, Triplex	D8D-1814C3, Triplex
Power And Type	4kw, 380V/50HZ, 1450rpm	5.5kw, 380V/50HZ, 2900rpm	5.5kw, 380V/50HZ, 1450rpm	7.5kw, 380V/50HZ, 1450rpm
Shipping Size	71x42.5x47.5cm	85x49x54cm	85x49x54cm	85x49x54cm
Shipping Weight	62kgs	77kgs	79kgs	82kgs

COMMERCIAL Cold Water ELECTRIC Pressure Washer

SMART CONTROL ELECTRIC PRESSURE WASHER

2.2-4KW 1&3Phase AC Motor, Plastic Cover, Smart Control, Commercial Grade



STANDARD FEATURES

- Compact and ergonomic design for easy storage and move.
- One-piece integrated modified PP cover, features high solid and high tenacity, colorfast and UV-resistant. Easy removable.
- Powder coating steel frame include hose, gun, and cable hook.
- Commercial grade triplex pump build with pressure gauge.
- 10" pneumatic wheel with bearing load.
- Professional trigger gun include with 20" stainless steel lance.
- 1/4" QD nozzle include 0, 15, 25, 40 degree and soap nozzle.
- ID5/16" (8mm) x 30FT (10m) steel braided, 3/8" Quick connect.
- Water proof electric motor smart control panel include over-load and electric leakage protection, indication lights.
- High quality 2.5M long electric cable, plug not include.

OPTIONAL ITEMS

- Remote Control TOTAL STOP system
- Solid Wheel
- Easy foam cannon
- Long cable and plug



One Piece Integrated Plastic Cover

- All covered with large ventilating, protects the motor from water splash and dust pollute. 4 bolts installed with no tools require, easy to remove for pump and motor maintain.



Metal Hook For Gun, Hose And Cable

- Two pieces aluminum symmetrical design hook, fo easy hang up the gun, high pressure hose and the electric cable.



Solid Wheel With No Bearing

- Solid non-flat 10" plastic wheel with no bearing load, tighten on the shaft with loose-proof nut. Shipping with wheel on.

Technical Specifications

Model	DCC-11/10CV-2S2	DCC-12/13CV-3S2	DCC-15/10CV-3T4	DCC-19/10CV-4T4
Max Pressure	1600psi/110bar	1740psi/120bar	2270psi/149bar	2810psi/194bar
Max Flow	2.2gpm/10.4lpm	3.3gpm/12.7lpm	2.7gpm/10.4lpm	2.6gpm/10.1lpm
Pump Model	D8C-1507C1, Triplex	D8C-1508C2, Triplex	D8C-1514C2, Triplex	D8C-1514C2, Triplex
Power And Type	2.2kw, 220V/50HZ, 2880rpm	3.0kw, 220w/50hz, 2880rpm	3.0kw, 380w/50hz, 1450rpm	4.0kw, 380w/50hz, 1450rpm
Shipping Size	70x48x50cm	70x48x50cm	70x48x50cm	70x48x50cm
Shipping Weight	45kgs	50kgs	50kgs	55kgs

COMMERCIAL Cold Water ELECTRIC Pressure Washer

HAND CARRY/PORTABLE ELECTRIC PRESSURE WASHER

1.1-1.5KW 100-220V 2&4 Pole Motor, Axial Pump, Commercial Grade



STANDARD FEATURES

- Professional grade brass forged axial pump, built with thermal protection and detergent injector, pressure adjustable.
- Performance proven heavy duty long lasting electric motor.
- Professional grade bottom type ON-OFF switch.
- Trigger gun include with short lance and variable nozzle.
- ID1/4" (6.4mm) x 25FT (8m) thermal plastic hose, M22 fitting.

Technical Specifications

Model	DCAA-9/6PH-1S2/60	DCAA-9/6PH-1S4/60	DCAA-10/7PH-1.5S4/60	DCAA-10/7PH-1.5S2/50
Max Pressure	1350psi/93bar	1380psi/95bar	1490psi/103bar	1490psi/103bar
Max Flow	1.53gpm/5.8lpm	1.5gpm/5.7lpm	2.0gpm/7.6lpm	2.0gpm/7.6lpm
Pump Model	DAA-1503C2, Axial, brass	DAA-1506C2, Axial, brass	DAA-1504C2, Axial, brass	DAA-15051C2, Axial, brass
Power And Type	1.1kw, 120V/60HZ, 3400rpm	1.1kw, 120V/60HZ, 1700rpm	1.5kw, 120V/60HZ, 3400rpm	1.5kw, 220V/50HZ, 2810rpm
Shipping Size	48x30x31cm	48x30x31cm	48x30x31cm	48x30x31cm
Shipping Weight	20.5kgs	21kgs	21.5kgs	21kgs

HAND CARRY/PORTABLE PRESSURE WASHER

1.1-1.5KW 100-220V 2&4 Pole Motor, Triplex Pump, Commercial Grade



STANDARD FEATURES

- Heavy duty grade brass forged triplex pump, features large side oil gauge and pressure adjustable.
- Performance proven heavy duty long lasting electric motor.
- Professional grade bottom type ON-OFF switch.
- Professional trigger gun include with short lance and variable nozzle.
- ID5/16" (8mm) x 30FT (10m) thermal plastic hose, 3/8" OD.



Technical Specifications

Model	DCC-9/6PH-1S4/60	DCC-10/7PH-1.5S4/60	DCC-10/7PH-1.5S2/50	DCC-10/7PH-1.5S4/50
Max Pressure	1330psi/92bar	1460psi/101bar	1520psi/105bar	1500psi/104bar
Max Flow	1.55gpm/5.9lpm	2.2gpm/7.7lpm	1.95gpm/7.4lpm	1.98gpm/7.5lpm
Pump Model	DBC-1506SC, Triplex	DBC-1508SC, Triplex	DBC-1505C, Triplex	DBC-1510C, Triplex
Power And Type	1.1kw, 120V/60HZ, 1700rpm	1.5kw, 120V/60HZ, 1700rpm	1.5kw, 220V/50HZ, 2610rpm	1.5kw, 220V/50HZ, 1450rpm
Shipping Size	48x30x31cm	48x30x31cm	48x30x31cm	48x30x31cm
Shipping Weight	24.5kgs	25kgs	24.5kgs	25kgs

COMMERCIAL Cold Water ELECTRIC Pressure Washer

HAND CARRY/PORTABLE ELECTRIC PRESSURE WASHER

1.5-2.2KW 220V/50HZ 2-4 Pole Motor, Triplex Pump, Commercial Grade



STANDARD FEATURES

- Heavy duty grade brass forged triplex pump, built with detergent injector, features large side oil gauge and pressure adjustable.
- Performance proven heavy duty long lasting electric motor.
- Professional grade twist type ON-OFF switch.
- Professional trigger gun include with short lance and variable nozzle.
- ID5/16" (8mm) x 30FT (10m) thermal plastic hose, 3/8" OD.


OPTIONAL ITEMS

- Pressure Gauge
- Quick Disconnect Nozzle Tips
- Turbo Nozzle
- Easy Foam Cannon
- Cable And Plug
- Carry on frame
- Pump Pre-fill
- With Oil

Technical Specifications

Model	DCC-15/7P-2S2/50	DCC-10/7P-1.5S2/50	DCC-10/7P-1.5S4/50
Max Pressure	2170psi/150bar	1520psi/105bar	1460psi/101bar
Max Flow	2.0gpm/7.6lpm	1.96gpm/7.4lpm	2.0gpm/7.7lpm
Pump Model	DBC-1505C, Triplex	DBC-1505C, Triplex	DBC-1510C, Triplex
Power And Type	2.2kw, 220V/50HZ, 2880RPM	1.5kw, 220V/50HZ, 2610RPM	1.5kw, 220V/50HZ, 1450RPM
Shipping Size	52.5x32x33.5cm	52.5x32x33.5cm	52.5x32x33.5cm
Shipping Weight	38kgs	33kgs	33kgs

Varies Safety Certified Plug For Optional



Frame Assy For Portable Pressure Washer

JE Series Frame Assy For Portable Pressure Washer

MODELS: DCC-10/7JE-1.5S2/50
DCC-10/7JE-1.5S4/50
DCC-15/7JE-2S2/50



COMMERCIAL HOT Water GAS & DIESEL Pressure Washer

3600PSI HOT WATER PRESSURE WASHER
Gas And Diesel Engine Powered, 12V Oil Fired Burner



STANDARD FEATURES

- Heavy Duty Grade Brass Forged Triplex Pump, Direct Drive, Built With Detergent Injector, Thermal Protection, Safety Pressure Relief And Pressure Gauge.
- Performance Proven Kohler Gasoline Engine Or Diesel Engine.
- Durable Heating Coil, Schedule 80 Pipe, Elliptically Wound & Stretched, No Seam Welds, Structurally Braced To Reduce Vibration & Pipe Wear, Sealed With A Ceramic Blanket, Stainless Steel Housing



OPTIONAL ITEMS

- High Pressure Base Mounting Hose Reel
- Turbo/rotatory Nozzle
- Rotatory Surface Cleaner
- Sands Blasting
- Drain Cleaning/Jetter Kit



Schedule 80 pipe Heating coil, elliptically wound and stretched, no seam welds

Work with engine recharging system 18Amp, eliminate the use of a generator.

WAYNE integrated 12V oil fired burner

Temperature control, adjustable thermostat

Model	DHEZ-3605GA	DHEZ-3605DA
Max Pressure	3600psi/248bar	3600psi/248bar
Max Flow	4.5gpm/17lpm	4.5gpm/17lpm
Pump Model	DBC-1510A, Direct Drive	DBC-1510A, Direct Drive
Power And Type	14hp/420cc, OHV	186FA/418cc, Diesel engine
Start Type	Key start, 18Amp recharging	Key start, 18Amp recharging
Battery	12V, 26AH	12V, 26AH
Gun And Lance	Hot water Trigger gun, insulated lance	Hot water Trigger gun, insulated lance
High Pressure Hose	ID8x10m, steel braided, hot water	ID8x10m, steel braided, hot water
Nozzle	5lips, OD nozzle	5lips, OD nozzle
Burner Fuel Tank	37.8 Liter(10Gal.)	37.8 Liter(10Gal.)
Fuel Consumption	8.1lph(2.14gph)	8.1lph(2.14gph)
Heating Coil	Steel, no seams welds, vertical, bottom fried	Steel, no seams welds, vertical, bottom fried
Burner And Type	WAYNE integrated with fan, 12V, adjustable thermostat	WAYNE integrated with fan, 12V, adjustable thermostat
Shipping Size	120x77x110cm	120x77x110cm
Shipping Weight	256kgs	290kgs

COMMERCIAL Hot Water Gas and Electric Motor Pressure Washer

2700-3600PSI GAS HOT PRESSURE WASHER
7-14HP Gas Engine, Triplex Pump Direct Drive, Hot Water Max 93°C/200°F



Model	DHA-2703	DHB-3605
Max Pressure	2700psi/186bar	3600psi/248bar
Max Flow	3.0gpm/11.3lpm	4.8gpm/18lpm
Pump Model	DBC-1507A, Direct Drive	DBC-1607A, Direct Drive
Power And Type	7hp/212cc, OHV	14hp/420cc, OHV
Start Type	Recoil start	Key start
Battery	N/A	12V 20AH
Gun And Lance	Hot water Trigger gun	Hot water Trigger gun
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Nozzle	5lips, OD nozzle	5lips, OD nozzle
Burner Fuel Tank	15liter (4gallon)	19liter (4gallon)
Fuel Consumption	5.8lph(1.58gph)	8.1lph(2.14gph)
Heating Coil	Vertical, top fried, dual spiral coil	Vertical, dual spiral coil
Shipping Size	96x76x112cm	112x73x124cm
Shipping Weight	130kgs	165kgs

2200-2500PSI ELECTRIC HOT PRESSURE WASHER

3-4Kw AC Motor, Triplex Pump Direct Drive, Hot Water Max 93°C/200°F

Model	DHM-2203	DHM-2503
Max Pressure	2200psi/152bar	2500psi/172bar
Max Flow	2.7gpm/10lpm	3.0gpm/11.3lpm
Pump Model	DBC-1507C, Direct Drive	DBC-1507C, Direct Drive
Power And Type	3Kw, Aluminum cage	4Kw, Aluminum cage
Voltage and HZ	220V/50HZ	380V/50HZ
Motor RPM	2Pole, 2880rpm	2Pole, 2900rpm
Gun And Lance	Hot water Trigger gun	Hot water Trigger gun
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Nozzle	5lips, OD nozzle	5lips, OD nozzle
Burner Fuel Tank	19liter (5gallon)	19liter (5gallon)
Fuel Consumption	4.9lph(1.3gph)	5.8lph(1.58gph)
Heating Coil	Vertical, top fried, dual spiral coil	Vertical, dual spiral coil
Shipping Size	108x78x110cm	96x100x70cm
Shipping Weight	155kgs	160kgs



INDUSTRIAL Cold Water GAS Multi-functional Pressure Washer

4000PSI MULTI-IN-ONE PRESSURE WASHER

13HP Gas Engine, All In On Pressure Washer For Multi Function And Task


The multi-functional Pressure Washer combines the pressure washer, rotating surface cleaner(21inch) and large water broom(4 nozzles) into one machine, with the ease of swapping between different cleaning mold by turn the high pressure ball valve. It can quick clean the large flat, vertical and hard-to-reach areas.

Ideal for street cleaning, car parks, events, driveways, paths, paved areas, tennis courts, sports grounds, decks and more.

The provide extension functions are for option, as water recovery, hose reel with long soft jetting hose (up to 60meter), you can extend the application for Multi cleaning task that with ALL-IN-ONE machine.



Standard Features



Quick Swap Between Different Cleaning Mold



Optional Extension Function



Technical Specifications

Model	DCQ-27/18MF	DCQ-27/17GRMF
Max Pressure	3900psi/270bar	4000psi/276bar
Max Flow	4.7gpm/18lpm	4.5gpm/17lpm
Pump Model	DBC-1807A5, Direct Drive	DBQ-1814G2, Gearbox reduction
Power And Type	13hp/390cc, OHV	13hp/390cc, OHV
Start Type	Key Start,	Key Start,
Battery	Battery 12V/20Ah	Battery 12V/20Ah
Gun And Lance	Trigger Gun, 20" Lance	Trigger Gun, 20" Lance
High Pressure Hose	ID8x10m, steel braided	ID8x10m, steel braided
Nozzle	5tps, 00 Nozzle	5tps, 00 Nozzle
Wheel Size & Type	Rear 10"Solid plus two front swivel castor	Rear 10"Solid plus two front swivel castor
Shipping Size	83x62x73cm	83x62x73cm
Shipping Weight	90kgs	93kgs


COMMERCIAL Cold Water GAS & DIESEL Drain/sewer/plumbing Jetter

3600-4000PSI DRAIN/SEWER JETTER

Gas And Diesel Engine Powered, Professional Grade

- Applicable Hose Up To ID 20CM, applicable for factory drainage, indoor drainage, small sewers, agricultural drainage, etc., can be widely used.
- Heavy-Duty triplex pump available with direct drive, belt drive or gearbox reduction, install with Pulse Valve.
- Gas engine 15hp/420cc OHV, electric start. 186FA/192FA Diesel engine is optional.
- Include Penetrate Nozzle at 15° and cleaning nozzle 30°. Set of soft jetting hose ID1/4"(6.4mm)×60m, one set removable hose reel with short connection hose. 10m High pressure hose and gun, foot penal valve and 12V 36 A/H battery.

Standard Features



35-45LPM DRAIN/SEWER JETTER

22hp Dual Cylinder Engine Powered, Professional Grade

- Applicable Hose Up To ID 30CM, powerful jet ideal for clearing large and more difficult lines, high water flow blast lines clear of grease, sediment, and debris.
- Heavy-Duty triplex pump available with direct drive, belt drive or gearbox reduction, install with Pulse Valve.
- Dual cylinder gas engine 22hp/680cc OHV air cooling, electric start, 25L fuel tank. .
- Include Penetrate Nozzle at 15° and cleaning nozzle 30°. Set of soft jetting hose ID3/8"(10mm)×60m, one set removable hose reel with short connection hose. 10m High pressure hose and gun, foot penal valve and 12V 36 A/H battery.

Optional Special Nozzle And Applications



Technical Specifications

Model	DCC-24/17S	DCQ-20/25GRS	DCQ-27/17GRS	DCF-24/34G8SG	DCF-18/45G8SG
Max Pressure	3800psi/248bar	3000psi/206bar	4000psi/276bar	3480psi/240bar	2610psi/180bar
Max Flow	4.5gpm/17lpm	6.5gpm/25lpm	4.5gpm/17lpm	9.0gpm/34lpm	11.5gpm/45lpm
Pump Model	DBC-1510A5, Direct drive	DBQ-2214G2, Gearbox	DBQ-1814G2, Gearbox	DBF-2221B, Belt drive	DBF-2821B, Belt drive
Power And Type	13hp/390cc, OHV,	15hp/420cc, OHV	45cc, Diesel engine	22hp/680cc, OHV	22hp/680cc, OHV
Start Type	Electric start with battery	Electric start with battery	Electric start with battery	Electric start with battery	Electric start with battery
Shipping Size	95x80x85cm	95x80x85cm	95x80x85cm	95x80x94cm	95x80x94cm
Shipping Weight	105kgs	110kgs	145kgs	145kgs	145kgs